



**FLUXX** 

The feed pan for successful broiler growing

### FLUXX – this feed pan with its many additional advantages ensures success



The arrow indicates which of the 7 feed level settings has been selected

= accurate and easy to read

The **FLUXX** is Big Dutchman's latest inn our popular BIG PAN 330, which has a in the market, the FLUXX offers many around the world, who have already t FLUXX meets the requirements of the the best possible way. You must see f

The FLUXX broiler feeding system not only satisfies the needs of dayold chicks but also those of heavy birds during the final growing period. How is this possible? During the first days of the growing period, the patent-pending **360° flooding feature** ensures a high feed level all the way around the pan – and all this without extra work! As birds grow, the entire feed line is raised causing the flooding mechanism to close and thus decreasing

### Advantages of the

Flooded FLUXX (flooding mechanism is activated in lowered position) => high feed level, ideal for day-old chicks

the feed pan is flooded when

it is standing in the litter or

on the ground = high feed level = ideal for day-old chicks pan either swinging freely or fix = always bird friendly

screwless snap-on system = simple and easy to assemble

5-arm or flexible 14-arn
 birds can easily feed from
 day-olds can easily get in

large pan rim with in = feed saver lip, feed w

smooth shape of rim = avoids chest bruising du

7 baffles rotate with t = feed waste is avoided = easy and thorough clea

> hinge-type fee = thorough clea

corrugated pan bottom subdivided into 14 sections = ideal for day-old chicks and small layer of litter

# sful rearing and growing, from day-old chicks to broilers ready for slaughter

novation in broiler feeding. Based on successfully maintained its position additional advantages. Experts from ested this new feed pan, confirm: the e different international markets in or yourself!

the feed level in the pans.

- The seven baffles integrated in the feed drop prevent the birds from throwing feed from side to side. Feed waste is therefore minimized very effectively.
- Depending on your requirements, different models of the FLUXX are available:
- with a 5-arm or a 14-arm grill
- with a deep, V-shaped pan or a corrugated pan subdivided into 14 sections.



FLUXX with corrugated bottom and 5-arm grill

Hygiene is of utmost importance! Just direct the high pressure cleaner into the feed pan so that it

starts to rotate. The feed pan can thus be cleaned thoroughly and efficiently. The result: a clean feed pan



## FLUXX at a glance

# Average figures for the use of the feed pan FLUXX

#### Broiler growing - ad-libitum feeding

- 1 feeding line per 4-5 m of house width, i.e.
- 9-12 m house width => 2 feeding lines
- 12-15 m house width => 3 feeding lines
- 15-18 m house width => 4 feeding lines

#### Number of birds/pan

up to 1.5 kg final weight: approx. 100 birds/pan up to 2.0 kg final weight: approx. 85 birds/pan up to 2.5 kg final weight: approx. 70 birds/pan up to 3.0 kg final weight: approx. 66 birds/pan up to 3.5 kg final weight: approx. 55 birds/pan

#### **Pullet rearing**

1.3-1.5 kg live weight: 60-45 birds/pan

#### Layer management

1.8-2.2 kg live weight: 45-30 birds/pan

These figures are average values and can vary depending on the breed, stocking density and climate. Please also seek advice from your bird supplier.

Please also consider differing applicable regulations from the specific rules of each country.



	Code No.	Description
0	11-31-4750	FLUXX with 5-arm grill and deep pan
0	11-31-4760	FLUXX with 5-arm grill and corrugated bottom
6	11-31-4700	FLUXX with 14-arm grill and deep pan
4	11-31-4710	FLUXX with 14-arm grill and corrugated bottom

# Technical data of the AUGERMATIC conveying system

- · Hopper with feed container
- Extension for feed container
- Maximum length of system
- Feed pipe with 2, 3, 4 holes
  Length of pipes
- Length of pipes
- Drive unit with gear motor
- · Conveying capacity
- Size of pellets
- Suspension

content approx. 115 I/75 kg content approx. 38 I/25 kg 150 m

Ø 45 mm

3000 mm + sleeve coupling

0.37/0.55 kW, 230/400 V, 50 Hz, 3 phases, 325 rpm special voltages on request

approx. 450 kg/h up to 4 mm central ceiling winch: - as hand winch

- as motor winch

The feeding system is only a small, but still very important part of the complete housing equipment for broiler growing farms. Please get to know our complete equipment program which also involves drinkers, climate control, stockpiling of feed. Good results and high performance can only be achieved if all the equipment in the system is compatible and easy to manage.



Germany Big Dutchman International GmbH Postfach 1163 · 49360 Vechta · Germany Tel. +49(0)4447-801-0 Fax +49(0)4447-801-237 E-Mail: big@bigdutchman.de

#### Asia

**Big Dutchman Asia** No. 25, Jalan Pemberita (U1/49) Temasya Industrial Park · Section U1 40150 Shah Alam · Selangor Darul Ehsan · Malaysia Tel. +60-3-556 923 20 · Fax +60-3-556 958 30 e-mail: bdasia@bda.com.my

**USA Big Dutchman, Inc.** P.O. Box 1017 · Holland, MI 49422-1017 · USA Tel. +1-616-3925981 Fax +1-616-3926188 e-mail: bigd@bigdutchmanusa.com



Picture of a house with AUGERMATIC lines